



Diesel Fuel Conditioner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 03/21/2016

Revision date: 08/30/2018

Supersedes: 11/07/2016

Version: 1.7

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : Diesel Fuel Conditioner
Product code : 94390

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Diesel additive

1.3. Supplier

Protex By Bardahl
1400 NW 52nd Street
P.O. Box 70607
Seattle, WA 98107
T 206-783-4851 - F 206-784-3219
jackie.leung@bardahl.com - www.bardahl.com

1.4. Emergency telephone number

Emergency number : 800-424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

| | |
|---|--|
| Flammable liquids, Category 4 | Combustible liquid |
| Acute toxicity (inhalation:dust,mist) Category 4 | Harmful if inhaled. |
| Skin corrosion/irritation, Category 2 | Causes skin irritation. |
| Germ cell mutagenicity, Category 1B | May cause genetic defects. |
| Carcinogenicity, Category 1B | May cause cancer. |
| Aspiration hazard, Category 1 | May be fatal if swallowed and enters airways. |
| Hazardous to the aquatic environment — Acute Hazard, Category 3 | Harmful to aquatic life |
| Hazardous to the aquatic environment — Chronic Hazard, Category 2 | Toxic to aquatic life with long lasting effects. |

2.2. GHS Label elements, including precautionary statements

GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Combustible liquid
May be fatal if swallowed and enters airways.
Causes skin irritation.
Harmful if inhaled.
May cause genetic defects.
May cause cancer.
Harmful to aquatic life
Toxic to aquatic life with long lasting effects.

Precautionary statements (GHS-US) :

Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Avoid breathing mist, vapours.
Wash hands thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Avoid release to the environment.
Wear eye protection, protective gloves.
If swallowed: Immediately call a POISON CENTER
If on skin: Wash with plenty of water
If inhaled: Remove person to fresh air and keep comfortable for breathing
Call a doctor if you feel unwell

Diesel Fuel Conditioner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Do NOT induce vomiting.
If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
In case of fire: Use BC-powder, carbon dioxide (CO₂), alcohol resistant foam to extinguish.
Collect spillage.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | GHS-US classification |
|--|----------------------|---------|---|
| Petroleum Distillates | (CAS-No.) 68476-34-6 | 50 - 80 | Flam. Liq. 4, H227 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Carc. 2, H351 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 |
| 2-ethylhexyl nitrate | (CAS-No.) 27247-96-7 | 5 - 10 | Flam. Liq. 4, H227 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Aquatic Acute 2, H401 Aquatic Chronic 2, H411 |
| Solvent naphtha (petroleum), heavy arom. | (CAS-No.) 64742-94-5 | 1 - 5 | Asp. Tox. 1, H304 Aquatic Acute 1, H400 |
| Solvent naphtha (light aromatic) | (CAS-No.) 64742-95-6 | 1 - 5 | Flam. Liq. 2, H225 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304 Aquatic Acute 3, H402 |
| 1,2,4-Trimethyl benzene | (CAS-No.) 95-63-6 | 0.1 - 5 | Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Acute 2, H401 Aquatic Chronic 2, H411 |
| Naphthalene | (CAS-No.) 91-20-3 | 0.1 - 1 | Acute Tox. 4 (Oral), H302 Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 |

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Irritation.
Symptoms/effects after ingestion : Risk of lung oedema.

Diesel Fuel Conditioner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Fire hazard : Combustible liquid.

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe mist, vapours. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist, vapours. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-ethylhexyl nitrate (27247-96-7)

Not applicable

Petroleum Distillates (68476-34-6)

| | | |
|-------|--------------------------------|-----------------------------|
| ACGIH | ACGIH TWA (mg/m ³) | 100 mg/m ³ 8 hrs |
|-------|--------------------------------|-----------------------------|

Solvent naphtha (petroleum), heavy arom. (64742-94-5)

Not applicable

Solvent naphtha (light aromatic) (64742-95-6)

Not applicable

Diesel Fuel Conditioner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| 1,2,4-Trimethyl benzene (95-63-6) | | |
|-----------------------------------|-----------------|--------|
| ACGIH | ACGIH TWA (ppm) | 25 ppm |

| Naphthalene (91-20-3) | | |
|-----------------------|-----------------|--------|
| ACGIH | ACGIH TWA (ppm) | 10 ppm |

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|---|
| Physical state | : Liquid |
| Colour | : amber |
| Odour | : characteristic |
| Odour threshold | : No data available |
| pH | : No data available |
| Melting point | : Not applicable |
| Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : 64.4 °C PMCC typical |
| Relative evaporation rate (butylacetate=1) | : No data available |
| Flammability (solid, gas) | : Not applicable. |
| Vapour pressure | : No data available |
| Relative vapour density at 20 °C | : No data available |
| Relative density | : No data available |
| Density | : 0.854 g/cm ³ typical |
| Solubility | : No data available |
| Log Pow | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Viscosity, kinematic | : 3.2 mm ² /s @ 40 C typical |
| Viscosity, dynamic | : No data available |
| Explosive limits | : No data available |
| Explosive properties | : No data available |
| Oxidising properties | : No data available |

9.2. Other information

No additional information available

Diesel Fuel Conditioner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
 Acute toxicity (dermal) : Not classified
 Acute toxicity (inhalation) : Inhalation:dust,mist: Harmful if inhaled.

| | |
|--------------------|---------------|
| ATE US (dust,mist) | 3.848 mg/l/4h |
|--------------------|---------------|

| 2-ethylhexyl nitrate (27247-96-7) | |
|-----------------------------------|--|
| LD50 oral rat | > 9600 mg/kg (Other, Rat, Male/female, Experimental value, (maximum attainable vapour concentration), Oral (repeated exposure), 14 day(s)) |
| ATE US (dermal) | 1100 mg/kg bodyweight |
| ATE US (gases) | 4500 ppmv/4h |
| ATE US (vapours) | 11 mg/l/4h |
| ATE US (dust,mist) | 1.5 mg/l/4h |

| Petroleum Distillates (68476-34-6) | |
|------------------------------------|-----------------------|
| LD50 oral rat | 7600 mg/kg |
| LD50 dermal rabbit | > 4300 mg/kg |
| LC50 inhalation rat (mg/l) | 4.1 mg/l/4h |
| ATE US (oral) | 7600 mg/kg bodyweight |
| ATE US (gases) | 4500 ppmv/4h |
| ATE US (vapours) | 4.1 mg/l/4h |
| ATE US (dust,mist) | 4.1 mg/l/4h |

| Solvent naphtha (petroleum), heavy arom. (64742-94-5) | |
|---|---------------------------------|
| LD50 oral rat | > 5000 mg/kg (Rat, Oral) |
| LD50 dermal rabbit | > 2000 mg/kg (Rabbit, Dermal) |
| LC50 inhalation rat (mg/l) | > 5 mg/l (4 h, Rat, Inhalation) |

| Solvent naphtha (light aromatic) (64742-95-6) | |
|---|-------------------------------|
| LD50 oral rat | > 2000 mg/kg (Rat, Oral) |
| LD50 dermal rabbit | > 3160 mg/kg (Rabbit, Dermal) |

| 1,2,4-Trimethyl benzene (95-63-6) | |
|-----------------------------------|--|
| LD50 oral rat | 6000 mg/kg bodyweight (EU Method B.1 tris: Acute oral toxic – Acute toxic class method, Rat, Male, Experimental value, Oral) |
| LD50 dermal rat | 3440 mg/kg (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male/female, Read-across, Dermal) |
| LC50 inhalation rat (mg/l) | 10.2 mg/l air (Other, 4 h, Rat, Male/female, Read-across, Inhalation) |
| ATE US (oral) | 6000 mg/kg bodyweight |
| ATE US (dermal) | 3440 mg/kg bodyweight |
| ATE US (gases) | 4500 ppmv/4h |
| ATE US (vapours) | 11 mg/l/4h |
| ATE US (dust,mist) | 1.5 mg/l/4h |

Diesel Fuel Conditioner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Naphthalene (91-20-3) | |
|-----------------------------------|------------------------------|
| LD50 dermal rat | > 2500 mg/kg (Rat, Dermal) |
| ATE US (oral) | 533 mg/kg bodyweight |
| Skin corrosion/irritation | : Causes skin irritation. |
| Serious eye damage/irritation | : Not classified |
| Respiratory or skin sensitisation | : Not classified |
| Germ cell mutagenicity | : May cause genetic defects. |
| Carcinogenicity | : May cause cancer. |
| Reproductive toxicity | : Not classified |
| STOT-single exposure | : Not classified |

| 1,2,4-Trimethyl benzene (95-63-6) | |
|--|---|
| STOT-single exposure | May cause respiratory irritation. |
| STOT-repeated exposure | : Not classified |
| Aspiration hazard | : May be fatal if swallowed and enters airways. |
| Viscosity, kinematic | : 3.2 mm ² /s @ 40 C typical |
| Symptoms/effects after skin contact | : Irritation. |
| Symptoms/effects after ingestion | : Risk of lung oedema. |

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects. Toxic to aquatic life.

| 2-ethylhexyl nitrate (27247-96-7) | |
|--|--|
| LC50 fish 1 | 2 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Brachydanio rerio, Semi-static system, Fresh water, Experimental value, GLP) |
| EC50 Daphnia 1 | > 12.6 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP) |
| ErC50 (algae) | 3.22 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP) |

| Solvent naphtha (petroleum), heavy arom. (64742-94-5) | |
|--|--|
| LC50 fish 1 | 2.34 mg/l (96 h, Oncorhynchus mykiss, Fresh water) |
| EC50 Daphnia 1 | 0.95 mg/l (48 h, Daphnia magna) |

| Solvent naphtha (light aromatic) (64742-95-6) | |
|--|-----------------------|
| LC50 fish 1 | 18 mg/l (Pisces) |
| EC50 Daphnia 1 | 21 mg/l (Daphnia sp.) |

| 1,2,4-Trimethyl benzene (95-63-6) | |
|--|---|
| LC50 fish 1 | 7.72 mg/l (96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal) |

| Naphthalene (91-20-3) | |
|------------------------------|---|
| LC50 fish 1 | 0.11 mg/l (96 h, Oncorhynchus mykiss, Literature study) |
| EC50 Daphnia 1 | 2.16 mg/l (48 h, Daphnia magna, Literature study) |

12.2. Persistence and degradability

| 2-ethylhexyl nitrate (27247-96-7) | |
|--|-------------------------------------|
| Persistence and degradability | Not readily biodegradable in water. |

| Solvent naphtha (petroleum), heavy arom. (64742-94-5) | |
|--|-------------------------------------|
| Persistence and degradability | Not readily biodegradable in water. |

| Solvent naphtha (light aromatic) (64742-95-6) | |
|--|---------------------------------|
| Persistence and degradability | Readily biodegradable in water. |

Diesel Fuel Conditioner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| 1,2,4-Trimethyl benzene (95-63-6) | |
|--|--|
| Persistence and degradability | Biodegradable in the soil. Not readily biodegradable in water. |
| Chemical oxygen demand (COD) | 0.44 g O ₂ /g substance |

| Naphthalene (91-20-3) | |
|---------------------------------|--|
| Persistence and degradability | Biodegradable in the soil. Readily biodegradable in water. |
| Biochemical oxygen demand (BOD) | 0 g O ₂ /g substance |
| Chemical oxygen demand (COD) | 0.22 g O ₂ /g substance |
| ThOD | 2.99 g O ₂ /g substance |

12.3. Bioaccumulative potential

| 2-ethylhexyl nitrate (27247-96-7) | |
|--|---|
| Log Pow | 5.24 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method) |
| Bioaccumulative potential | High potential for bioaccumulation (Log Kow > 5). |

| Solvent naphtha (petroleum), heavy arom. (64742-94-5) | |
|--|---------------|
| Log Pow | 2.9 - 6.1 |
| Bioaccumulative potential | Bioaccumable. |

| Solvent naphtha (light aromatic) (64742-95-6) | |
|--|---------|
| Log Pow | 2.1 - 6 |

| 1,2,4-Trimethyl benzene (95-63-6) | |
|--|--|
| BCF fish 1 | 31 - 275 (Other, 8 week(s), Cyprinus carpio, Weight of evidence) |
| Log Pow | 3.63 - 4.09 (Experimental value) |
| Bioaccumulative potential | Low potential for bioaccumulation (BCF < 500). |

| Naphthalene (91-20-3) | |
|------------------------------|---|
| BCF fish 1 | 23 - 168 (8 week(s), Cyprinus carpio, Literature study) |
| Log Pow | 3.3 (Experimental value) |
| Bioaccumulative potential | Low potential for bioaccumulation (BCF < 500). |

12.4. Mobility in soil

| 2-ethylhexyl nitrate (27247-96-7) | |
|--|--|
| Log Koc | 3.75 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP) |
| Ecology - soil | Low potential for mobility in soil. |

| 1,2,4-Trimethyl benzene (95-63-6) | |
|--|---|
| Surface tension | 0.029 N/m |
| Log Koc | 3.04 (log Koc, Calculated value) |
| Ecology - soil | Low potential for mobility in soil. May be harmful to plant growth, blooming and fruit formation. |

| Naphthalene (91-20-3) | |
|------------------------------|------------------------|
| Surface tension | 0.03 N/m (100 °C) |
| Ecology - soil | Adsorbs into the soil. |

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Diesel Fuel Conditioner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not applicable

Transportation of Dangerous Goods

Not applicable

Transport by sea

| | |
|---------------------------------------|---|
| Transport document description (IMDG) | : UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III, MARINE POLLUTANT |
| UN-No. (IMDG) | : 3082 |
| Proper Shipping Name (IMDG) | : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. |
| Class (IMDG) | : 9 - Miscellaneous dangerous substances and articles |
| Packing group (IMDG) | : III - substances presenting low danger |
| Limited quantities (IMDG) | : 5 L |
| Marine pollutant | : Yes |



Air transport

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Diesel Fuel Conditioner

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

2-ethylhexyl nitrate (27247-96-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Solvent naphtha (petroleum), heavy arom. (64742-94-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Solvent naphtha (light aromatic) (64742-95-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

1,2,4-Trimethyl benzene (95-63-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

Diesel Fuel Conditioner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Component | State or local regulations |
|--|--|
| 2-ethylhexyl nitrate(27247-96-7) | |
| Solvent naphtha (petroleum), heavy arom.(64742-94-5) | |
| Solvent naphtha (light aromatic)(64742-95-6) | |
| 1,2,4-Trimethyl benzene(95-63-6) | U.S. - New Jersey - Right to Know Hazardous Substance List |
| Naphthalene(91-20-3) | |
| Petroleum Distillates(68476-34-6) | |

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 08/30/2018

Full text of H-statements:

| | |
|------|---|
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H227 | Combustible liquid |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H312 | Harmful in contact with skin. |
| H315 | Causes skin irritation. |
| H319 | Causes serious eye irritation. |
| H332 | Harmful if inhaled. |
| H335 | May cause respiratory irritation. |
| H340 | May cause genetic defects. |
| H350 | May cause cancer. |
| H351 | Suspected of causing cancer. |
| H400 | Very toxic to aquatic life. |
| H401 | Toxic to aquatic life |
| H402 | Harmful to aquatic life |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |

NFPA health hazard


: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard

: 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



Diesel Fuel Conditioner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F but below 200 F. (Classes II & IIIA)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal protection

: B

B - Safety glasses, Gloves

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product